



PCT/GB 2004 / 0 0 2 7 1 2



INVESTOR IN PEOPLE

The Patent Office

Concept House

Cardiff Road

Newport REC'D 14 JUL 2004

South Wales

NP10 8QQ

PCT

**PRIORITY
DOCUMENT**

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

I also certify that the attached copy of the request for grant of a Patent (Form 1/77) bears an amendment, effected by this office, following a request by the applicant and agreed to by the Comptroller-General.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed


Re Behen

Dated

6 July 2004

BEST AVAILABLE COPY

Patents Form 1/77

Patents Act 1977
(Rule 16)25JUN03 E617815-1 C78956
P01/7700 0.00-0314817.8**Request for grant of a patent**

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form.)

The Patent Office

Cardiff Road
Newport
South Wales
NP10-8QQ

1. Your reference

SP 2020

2. Patent application number

(The Patent Office will fill in this part)

0314817.8

25 JUN 2003

3. Full name, address and postcode of the or of each applicant (underline all surnames)

Southampton Photonics Ltd
Plu House
Enterprise Road
Chilworth Science Park
Southampton

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation UK

SO16 7NS

7894330002

4. Title of the invention

Apparatus for providing optical radiation.

5. Name of your agent (if you have one)

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

GRAHAM JONES & COMPANY
77 BEACONSFIELD ROAD
BLACKHEATH, LONDON
SE3 7LG

P01 23.6.04

Patents ADP number (if you know it)

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d))

Patents Form 1/77

0072840 25-JUN-03 05:20

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description 11

Claim(s) 3

Abstract

Drawing(s) 5

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77)

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

11.

I/We request the grant of a patent on the basis of this application.

Signature



Date 25 June 2002

12. Name and daytime telephone number of person to contact in the United Kingdom

Malcolm Varnham 02380 765 417

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

- 1 -

Apparatus for Providing Optical Radiation

Field of Invention

This invention relates to an apparatus for providing optical radiation. The invention can take various forms, for example a laser, an optical amplifier, a source of amplified spontaneous emission, or a master oscillator power amplifier. The invention has application for materials processing.

Background to the Invention

Pulsed NdYAG lasers are widely used in industrial processes such as welding, cutting and marking. Care has to be taken in these processes to ensure that the plasmas generated by the laser does not interfere with the incoming laser pulses. The relatively low pulse repetition rates (6kHz) at high peak powers that are achievable in a NdYAG laser have led to their wide application in laser machining.

Fibre lasers are increasingly being used for materials processing applications such as welding, cutting and marking. Their advantages include high efficiency, robustness and high beam quality. Examples include femtosecond lasers for multiphoton processing such as the imaging of biological tissues, Q-switched lasers for machining applications, and high-power continuous-wave lasers. Their disadvantage is their relatively low energy storage capacity as compared to NdYAG lasers.

In many applications, fibre lasers need to compete with the more mature diode pumped solid state lasers. In order to do so, much greater optical powers need to be achieved, with high reliability and lower cost.

- 2 -

Fibre lasers are typically longer than diode-pumped solid state lasers, and this leads to non-linear limitations such as Raman scattering becoming problematical. It would be advantageous to have fibre lasers that are shorter.

Fibre lasers are typically pumped with diode lasers in bar or stack form. The output from bars and stacks is not ideally matched to the geometry of fibre lasers, leading to a loss in brightness, and thus the need to increase the length of cladding pumped fibre lasers in order to obtain the necessary absorption and output energy.

Cladding pumped fibre lasers that have been described in the prior art have inner claddings that are either rectangular, have flats machined on them, have a shape such as a polygon, or are asymmetric. None of these shapes provides high coupling of cladding modes with the core modes whilst also combining a substantially regular geometry with curved outside edges that is suitable for coupling radiation from substantially round sources.

An aim of the present invention is to provide an apparatus for providing optical radiation that reduces the above aforementioned problem.

Summary of the Invention

According to a non-limiting embodiment of the present invention, there is provided apparatus for providing optical radiation, which apparatus comprises an optical fibre having core, a first cladding and a second cladding, in which the first cladding has a substantially constant diameter.

The first cladding may be non-circular.

The first cladding may have at least one axis of mirror symmetry.

The first cladding may have a geometric centre. The core may be located at the geometric centre. The core may be offset from the geometric centre.

- 3 -

The core may be centred at the centre of the smallest imaginary circle that can contain the first cladding. Alternatively, the core may be offset from the centre of the largest imaginary circle that can be contained within the first cladding.

The first cladding may comprise circular arcs having centres at the vertices of an equilateral star. The circular arcs may have a first radius equal to the length of the side of the star. The circular arcs may each have a first radius greater than the length of the side of the star, which circular arcs are joined by circular arcs each having a centre located at the vertices, and a second radius equal to the difference between the first radius and the length of the side of the star.

Each line of the star preferably crosses all the other lines of the star. The star may be an equiangular star. Alternatively, the star may contain at least two different angles.

The star preferably contains an odd number of vertices.

The fibre may contain at least one longitudinally extended hole. The hole may be circular. Alternatively, the hole may be non-circular.

The fibre may contain at least one region of low refractive index. The region of low refractive index may be circular. Alternatively, or in addition, the region of low refractive index may be non-circular.

The fibre may comprise rare-earth dopant. The rare earth doping may be selected from the group comprising Ytterbium, Erbium, Neodymium, Praseodymium, Thulium, Samarium, Holmium and Dysprosium, or is Erbium codoped with Ytterbium, or is Neodymium codoped with Ytterbium.

The apparatus may comprise a pump source for providing pump radiation coupled to the first cladding.

The apparatus may be in the form of a laser, an amplifier, a source of amplified spontaneous emission or a master oscillator power amplifier.

Brief Description of the Drawings

Embodiments of the invention will now be described solely by way of example and with reference to the accompanying drawings in which:

Figure 1 shows an apparatus for providing optical radiation according to the present invention;

Figure 2 shows rays being internally reflected by a first and a second cladding;

Figures 3 and 4 show first claddings based on a star with three vertices;

Figures 5 and 6 show first claddings based on an equiangular star with five vertices;

Figures 7 and 8 show first claddings based on a star with five vertices which first cladding has an axis of mirror symmetry;

Figures 9 and 10 show first claddings with no axis of mirror symmetry;

Figure 11 shows a fibre containing a core at the geometric centre of the first cladding;

Figure 12 shows a fibre containing a core offset from the geometric centre of the first cladding;

Figure 13 shows a fibre containing a core that is centred on the centre of the smallest imaginary circle that contains the first cladding;

Figure 14 shows a fibre having a circular first cladding and a longitudinally extending hole;

- 5 -

Figure 15 shows a fibre having a circular first cladding and a region of low refractive index;

Figure 16 shows a fibre having a non-circular first cladding and a longitudinally extending hole;

Figure 17 shows a fibre having a non-circular first cladding and a region of low refractive index;

Figure 18 shows apparatus in the form of a laser;

Figure 19 shows apparatus in the form of an optical amplifier;

Figure 20 shows apparatus in the form of a source of amplified spontaneous emission; and

Figure 21 shows apparatus in the form of a master oscillator power amplifier.

- 5 -

Detailed Description of Preferred Embodiments of the Invention

With reference to Figure 1, there is provided apparatus for providing optical radiation, which apparatus comprises an optical fibre 5 having a core 3, a first cladding 1 and a second cladding 2, in which the first cladding 1 has a substantially constant diameter 9.

By diameter 9 it is meant the diameter or width of the first cladding 1.

It is preferred that the refractive index of the core is greater than the refractive index of the first cladding 1 which has a higher refractive index than the second cladding 2. The first cladding 1 may be a glass such as a silica, doped silica, or a phosphate glass. The second cladding 2 may be a polymer, silica, a doped silica, a fluorosilicate, or a doped phosphate glass. If the second cladding 2 is a glass, then it is preferred that the second cladding 2 is coated with a polymer.

The shape of the first cladding 1 shown in Figure 1 is known as a Realeaux triangle. It is non-circular, and has the property that it has constant diameter. It has three vortices 6, each of which acts as the centre for the opposite circular arc 7 which connects adjacent vortices 6.

An advantage of utilizing such a first cladding 1 is illustrated in Figure 2 which shows a light ray 20 (assumed propagating longitudinally along the fibre 5) being totally internally reflected at the interface 21 between the first cladding 1 and the second cladding 2. In a circular fibre, the ray 20 would be a so-called whispering gallery mode, reflecting at a uniform angle, and never intersecting the core 3. However, utilizing the Realeaux triangle, the ray 20 reflects at higher angles such that it intercepts the core 20 several times in the example shown. The result is a higher degree of overlap of rays propagating along the first cladding 1 with the core 3, which

- 7 -

is advantageous for a cladding pumped fibre laser or amplifier because this equates to a shorter length over which pump energy is absorbed by the core 3.

Further examples of the first cladding 1 are first claddings 31, 41, 51, 61, 71, 81, 91, and 101 shown in Figures 3 to 10. The first claddings 31, 41, 51, and 61 have both rotational and mirror symmetry. The first claddings 71 and 81 have only one axis 77 of mirror symmetry. The first claddings 91 and 101 shown in Figures 9 and 10 have no axis of mirror symmetry.

Referring to Figure 3, the first cladding 31 is defined by an equilateral star 32 comprising three lines 33, three vertices 35, and defined by a first length 34 equal to the length of the side of the star 32. The first cladding 31 comprises circular arcs 36 connecting adjacent vertices 35, the circular arcs 36 having centres 37 at the vertices 35 of the equilateral star 32. The circular arcs 35 have a first radius 38 equal to the first length 34.

Figure 4 shows a first cladding 41 defined by circular arcs 42 and 43. The circular arcs 42 are centred on the vertices 35, have a first radius 38 that is greater than the first length 34, and connect adjacent lines 33. The circular arcs 42 are joined together with circular arcs 43 each centred at the vertices 35 and each having a second radius 44 equal to the difference between the first radius 38 and the first length 34.

Figures 5 and 6 show first claddings 51 and 61 similar to the first claddings 31 and 41 respectively, but with five vertices 35 instead of three vertices 35. The equilateral stars 32 shown in Figures 3, 4, 5 and 6 are equiangular stars.

Figures 7 and 8 show first claddings 71 and 81 similar to first claddings 51 and 52 respectively, but where the equilateral stars 32 contain at least two different

- 8 -

angles 75, 76, that is, the equilateral stars 32 are not equiangular stars. The first claddings 71 and 81 contain an axis of mirror symmetry 77.

Figures 9 and 10 show first claddings 91 and 101 defined by equilateral stars 32 characterised in having no axes of mirror symmetry.

The stars 32 shown in Figures 3 to 10 all have an odd number of vertices 35. In general the number of vertices 35 should be odd, and can be between three and one hundred and three, but is preferably between three and nine.

Each of the lines 33 that make up the stars 32 in Figures 3 to 10 cross each of the other lines 33.

Figure 11 shows a fibre 110 containing the first cladding 51. The core 3 is located at the geometric centre 111 of the first cladding 51 that is defined by the intersect of two of the lines of mirror symmetry 77. As shown by the fibre 120 of Figure 12, the core 3 can also be offset from the geometric centre 111. The cores 3 in both Figures 11 and 12 are shown as being concentric with the second cladding 2 which can sometimes be convenient for locating the core 3 and/or for splicing the fibre 110, 120, especially if the second cladding 2 is made from a hard material such as a glass.

The first claddings 91 and 101 shown with reference to Figures 9 and 10 do not have lines of mirror symmetry 77 and do not have geometric centres. Figure 13 shows a fibre 130 comprising the first cladding 101. A circle 131 is defined which is the smallest circle that can contain the first cladding 101. The core 3 may be centred at the centre 132 of the circle 131. This location is advantageous for splicing the fibre 130. Alternatively, the core 3 may be offset from the centre of the circle 131 which in certain configurations may be advantageous for maximising the overlap between cladding modes and the core. Figure 14 shows a fibre 140 comprising a circular first

- 9 -

cladding 141 which contains a longitudinally extended hole 142. The hole 142 may be circular or non-circular. The hole 142 may be elliptical or substantially rectangular. The hole 142 will assist in coupling cladding modes with the core 3.

Figure 15 shows a fibre 150 containing a region 151 of low refractive index in the first cladding 141. By low refractive index, it is meant that the refractive index of the region 151 is less than that of the first cladding 141. The region 151 of low refractive index may be circular. Alternatively, or in addition, the region 151 of low refractive index may be non-circular. The region 151 of low refractive index may be boron doped silica, and may be a stress rod manufactured using modified vapour chemical deposition.

Figures 16 and 17 show similar fibres 160, 170 to those shown in Figures 14 and 15 but with the non-circular first cladding 51.

With reference to Figure 1, the fibre 5 preferably comprises rare-earth dopant 10. The rare earth dopant 10 may be selected from the group comprising Ytterbium, Erbium, Neodymium, Praseodymium, Thulium, Samarium, Holmium and Dysprosium, or is Erbium codoped with Ytterbium, or is Neodymium codoped with Ytterbium. The rare earth dopant 10 may be located in the core 3, in the first cladding 1, or in both the core 3 and the first cladding 1. Fibres 110, 120, 130, 140, 150, 160 and 170 preferably contain rare-earth dopant 10.

Fibres containing a first cladding 1 as described with reference to the above figures can be fabricated by inserting a modified chemical vapour deposition perform into a pre-machined glass capillary having the desired outer contour and materials properties. The machining can be performed using ultrasonic milling and/or lapping.

Figure 18 shows apparatus for providing optical radiation 189 in the form of a laser 180 comprising a fibre 181 and a pump source 182 for providing pump radiation

- 10 -

185 to the first cladding 1, and first and second reflectors 183, 184. The fibre 181 is preferably one of the fibres described with reference to Figures 1 to 17 that contains rare earth dopant 10. The pump source 182 can comprise at least one semiconductor laser diode, a laser diode bar or a laser diode stack. The reflectors 183 and 184 can comprise a fibre Bragg grating, a grating, a dichroic mirror, or an end reflection from the fibre 181. It is preferable that the reflection of the first reflector 183 is greater than the reflection of the second reflector. The first reflector 183 is preferably dichroic, reflecting light at the wavelength of the optical radiation 189, and transmitting the pump radiation 185. The fibre 181 can be multimode or monomode optical fibre.

Figure 19 shows apparatus for providing optical radiation 195 in the form of an optical amplifier 190. The amplifier 190 is similar to that shown in Figure 18 except that there are no reflectors 183, 184. Pump radiation 185 and signal 191 are coupled into the fibre 181 by a coupler 193. The coupler 193 may be any form of optical combining means such as a beam splitter or coupler, but is preferably a dichroic mirror or wavelength division multiplexing coupler. The optical amplifier 190 can include one or more isolators 196.

Figure 20 shows apparatus for providing optical radiation 205 in the form of a source of amplified spontaneous emission 200 that comprises the pump source 182 and the fibre 181. The source 200 may also contain one or both of the isolator 196 and reflector 183.

Figure 21 shows apparatus for providing optical radiation 215 in the form of a master oscillator power amplifier 210 comprising the pump source 182, the fibre 181, and a seed source 211 for providing an optical seed 212. The seed source 211 may be a semiconductor laser, a pulsed laser, a fibre laser, or a solid state laser. A

- 11 -

semiconductor laser is often desirable in this application because the amplitude of the optical seed 212, and hence the optical radiation 215 can be controlled to a desired shape by modulating the drive current into the semiconductor laser. The provision of the isolator 196 is optional.

The laser 180, the amplifier 190, the source of amplified spontaneous emission 200, and the master oscillator power amplifier 210 are believed to have important application as sources of high power laser radiation for industrial and aerospace applications including materials processing. In such applications it is often desirable to synchronise the pump source 182 with the movement of an optical scanner.

It is to be appreciated that the embodiments of the invention described above with reference to the accompanying drawings have been given by way of example only and that modifications and additional components may be provided to enhance performance.

The present invention extends to the above-mentioned features taken in isolation or in any combination.

- 12 -

Claims

1. Apparatus for providing optical radiation, which apparatus comprises an optical fibre having core, a first cladding and a second cladding, in which the first cladding has a substantially constant diameter.
2. Apparatus according to claim 1 in which the first cladding is non-circular.
3. Apparatus according to claim 1 or claim 2 in which the first cladding has at least one axis of mirror symmetry.
4. Apparatus according to any one of the preceding claims in which the first cladding has a geometric centre.
5. Apparatus according to claim 4 in which the core is located at the geometric centre.
6. Apparatus according to claim 4 in which the core is offset from the geometric centre.
7. Apparatus according to any one of claims 1 to 3 in which the core is centred at the centre of the smallest imaginary circle that can contain the first cladding.
8. Apparatus according to any one of claims 1 to 3 in which the core is offset from the centre of the largest imaginary circle that can be contained within the first cladding.
9. Apparatus according to any one of the preceding claims, in which the first cladding comprise circular arcs having centres at the vertices of an equilateral star.
10. Apparatus according to claim 9 wherein the circular arcs each have a first radius equal to the length of the side of the star.
11. Apparatus according to claim 9 in which the circular arcs each have a first radius greater than the length of the side of the star, which circular arcs are

- 13 -

joined by circular arcs having a centre located at the vertices, and a second radius equal to the difference between the first radius and the length of the side of the star.

12. Apparatus according to any one of claims 9 to 11 in which each line of the star crosses all the other lines of the star.
13. Apparatus according to claim 12 in which the star is an equiangular star.
14. Apparatus according to claim 12 in which the star contains at least two different angles.
15. Apparatus according to any one of claims 9 to 14 in which the star contains an odd number of vertices.
16. Apparatus according to any one of the preceding claims in which the fibre contains at least one longitudinally extended hole.
17. Apparatus according to claim 16 in which the hole is circular.
18. Apparatus according to claim 16 in which the hole is non-circular.
19. Apparatus according to any one of the preceding claims in which the fibre contains at least one region of low refractive index.
20. Apparatus according to claim 19 in which the region of low refractive index is circular.
21. Apparatus according to claim 19 in which the region of low refractive index is non-circular.
22. Apparatus according to any one of the preceding claims wherein the fibre comprises rare-earth dopant.
23. Apparatus according to claim 22 in which the rare earth doping is selected from the group comprising Ytterbium, Erbium, Neodymium, Praseodymium.

- 14 -

Thulium, Samarium, Holmium and Dysprosium, or is Erbium codoped with Ytterbium, or is Neodymium codoped with Ytterbium.

24. Apparatus according to any one of the preceding claims and comprising a pump source for providing pump radiation coupled to the first cladding.
25. Apparatus according to any one of the preceding claims which apparatus is in the form of a laser, an amplifier, a source of amplified spontaneous emission, or a master oscillator power amplifier.
26. Apparatus substantially as herein described with reference to the accompanying drawings.

1 / 5




FIG 1




FIG 2




FIG 3




FIG 4




FIG 5




FIG 6

215




FIG 7




FIG 8




FIG 9




FIG 10

3 / 5




FIG 11




FIG 12




FIG 13

4 / 5




FIG 14




FIG 15




FIG 16








FIG 17

5 / 5



**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☒ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.